

JUMBO INDIRECT OIL FIRED HEATERS RANGE

Jumbo indirect oil fired high capacity heaters range in size from 110kw - 235kw. Great for providing temporary heat for large marquees, construction sites, large building temperature control & dry-out and many more applications. The unit is placed outside and large volumes of warm, clean air are ducted into the area. A large range of accessories are available to suit any temporary heating application including ducting, fuel & power management, thermostatic controls and duct splitters. Call us now to get the right heating solution for your job.



SPECIFICATIONS

		Jumbo 110M	Jumbo 185M	Jumbo 235M	Jumbo 185T	Jumbo 235T
Rated Heat Power	KW	110.45	185.54	235.72	185.54	235.72
	kcal/h	94.999	159.583	202.715	159.583	202.715
	BTU/h	379.995	638.294	810.861	638.294	810.861
Output Heat Power	KW	102.51	171.07	216.86	171.07	216.86
	kcal/h	88.199	147.117	180.499	147.117	180.499
	BTU/h	352.636	588.470	745.992	588.470	745.992
Heat Efficiency	%	92.8	92.2	92	92.2	92
Air Flow	m ³ /h	9000	13000	17000	13000	17000
Available Static Pressure	Pa mm H ₂ O	49	57	56	57	56
Effective Heat Range	m	47	54	60	54	60
Oil Consumption	kg/h	8.74	14.58	18.65	14.58	18.65
Electrical Power	V - ph - Hz	230-1-50	230-1-50	230-1-50	400-3-50	400-3-50
Power Consumption	W	1100	1550	2550	1550	2550
Flue	mm	150	200	200	200	200
Outlet Hose max (mm / m)	1 OUTLET	500-25	700-25	700-30	700-25	700-30
	2 OUTLETS	400-15	500-15	600-15	500-15	600-15
	4 OUTLETS	-	350-15	400-15	350-15	400-15
Outlet Snorkel	mm / m	100-5	100-5	100-5	100-5	100-5
Inlet Hose	mm / m	570-6	650-6	720-6	650-6	720-6